

Specification Sheet for DL500 Range

Company Name:	Date:
Order Number:	Quantity required:
Deliver Lift Collect Lift from Del	Delivery Date Required:
Delivery Address	
Company Name:	Street Address:
Post Code:	City:
Vehicle Details	
Is the Vehicle a Factory Body?	
If yes, please state Vehicle Make & Model:	
Door type (If Barn Door, please fill in Cam Centre Dim below) ☐ Roller Shutter ☐ Barn Doors ☐ Curtain Sider ☐ Dropside	
Cam Centres: mm	
Above Floor Lift required? Yes No (If Yes please fill in above Floor Dim below)	
Above Floor Dim required: mm	В ————
Dimension A (Vehicle Floor Height):	- mm
Dimension B (Overall Width of Vehicle):	_ mm
Dimension C (Loading Aperture):	_ mm
Dimension D (Width of Corner Post):	– mm
Vehicle Voltage	
☐ 12v ☐ 24v	
Chassis Mass:	
If above 3.5T, Whole Vehicle Type Approval number	r and bracing required for lift?
☐ Yes ☐ No	



Tail Lift Details Lift Capacity: 500kg 750kg **Platform Working Area:** 42"(1065mm) 48"(1220mm) 54"(1370mm) 32"(815mm) 36"(915mm) 60" (1525mm) Only available on 750kg Lifts. Rear Ramp Type: Fixed Leading Edge 8" (205mm) Fixed Leading Edge C/W Trolley Stops 10" (250mm) Pair of Hinged Ramps 9" (225mm) **Side Ramp Type:** Pair of Hinged Side Ramps (Only available on 42" Platform with Hinged Rear Ramps) Pair of Detachable Side Ramps Single Detachable Side Ramp **Control Setup:** Single Fixed Control Single Detachable Wanderlead Internal Hard Wired Wanderlead and Fixed External Control **Dual Fixed Controls** Tail Lift Isolator: Red Key Isolator Cab Switch Fence Type: Auto Erect Fences (If required, Lift will require Short Columns and Dual Fixed Controls) N/S Drop in Fence O/S Drop in Fence Pair of Drop in Fences Sockets only for Drop in Fences Pair of Wrap around Fences **Options:** Stow Light Indicator Flashing Lights Short Column (WVTA) Left Hand Drive Two Handed Control To be completed by DEL Part Number of Lift: _

Price of each Lift: