



Specification Sheet for S1000 / S1500 Range

Company Name:	Date:
Order Number:	Quantity required:
☐ Deliver Lift ☐ Collect Lift from Del	Delivery Date Required:
Delivery Address:	
Company Name:	Street Address:
Post Code:	City:
Vehicle Details	
	NOT suitable for Dropside / Flatbed Bodies. below)
Roller Shutter Barn Doors Curtainsider	
Cam Centres: mm	
Suspension Type:	
Steel Air	- B
Dimension A (Unladen Vehicle Floor Height):	——— mm (Max 1470mm)
Dimension A (Laden Vehicle Floor Height):	mm (Min 1100mm
Dimension B (Overall Width of Vehicle):	- mm
Dimension C (Loading Aperture):	- mm
Dimension D (Width of Corner Post):	– mm
Vehicle Overhang mm	G R O U N D
Tail Lift Width Required:	
☐ 2412mm ☐ 2457mm ☐ 2487mm* ☐ 2	2512mm
*Please Note: 2487mm is the max width allowed for Lifts	with Dual Mode Fences as they protrude 30mm per side.
Vehicle Voltage:	
24v	
Whole Vehicle Type Approval underun and bracing	required?
□ Ves □ N	





Tail Lift Details

Lift Capacity:
☐ 1000kg ☐ 1500kg
Platform Specification:
1065mm + 3 Way Folding Ramps
1220mm + 3 Way Folding Ramps
1525mm + 3 Way Folding Ramps
Side Ramp Type:
Pair of Hinged Side Ramps (Please note: These Ramps protrude the Columns by 18mm per side).
Control Setup
Control Setup:
Dual Fixed Controls Single Detachable Wanderlead Internal Hard Wired Wanderlead and Fixed External Control
Tail Lift Isolator: (Not required with Single Detachable Wanderlead).
☐ Cab Switch ☐ Red Key Isolator
Cable Options:
35' Battery Cables (Standard) 45' Battery Cables 35' Trailer Wiring 45' Trailer Wiring
Fence Type:
☐ Dual Mode Fences ☐ Pair of Detachable Fences ☐ Fence Socket Kit (No Fences)
Options:
☐ Battery Guard ☐ Flashing Lights ☐ Stow Light Indicator ☐ Two Handed Control
☐ Left Hand Drive ☐ Service Kit
Warranty options: (12 month Warranty as standard)
2 Year Warranty 3 Year Warranty 4 Year Warranty 5 Year Warranty
To be completed by DEL
Part Number of Lift: ———
Price of each Lift:



