


EFFER
iX.B55^{HP}
TECHNICAL DATA SHEET

32.1tm range loader crane

- SPACEevo control system.
- Variable pump, for increased flow performances and reduced fuel consumption.
- Nano based technology coating.
- CE marked.

Standard and optional features:

- XS Drive remote control (s).
- CombiDrive 4 remote control (o).
- E-5 and E-6 versions with optional JIB 70X4.

Description	Unit	E-4	E-5	E-5 JIB70X4	E-6	E-6 JIB70X4	E-7	E-8
Max. net lifting moment	kgm/ kNm	314/32.1	307/31.3	307/31.3	301/30.7	301/30.7	296/30.2	292/29.8
Slewing arc	(°)	420	420	420	420	420	420	420
Slewing capacity-max slope	(°)	3	3	3	3	3	3	3
Max oil delivery	l/min	100-140	100-140	100-140	100-140	100-140	100-140	100-140
Max. outreach, hydraulic extensions	m	11.7	13.9	-	16.2	-	18.6	21.0
Max. Outreach, with manual extension	m	-	-	-	-	-	-	-
Outreach, with JIB	m	-	-	23.9	-	26.0	-	-
Outreach, with JIB, with manual extension	m	-	-	25.9	-	28.0	-	-
Weight standard crane (±2%), incl supporting legs	kg	4036	4232	5060	4402	5227	4571	4694

(s) = Standard, (o) = Optional