

SIDE LOADER GATE

3,300 lb. - 4,400 lb. Capacities



Large, Side Loading Platform - Special Application Food Distribution Gate

*Products shown may feature optional equipment.
Content subject to change without notice.*

PLATFORM

- 1/2 Steel (main), 1/2 Aluminum (folding)
- Large, Single-Fold, Level Ride
- Stores completely under trailer

STANDARD GTSL SERIES ADVANTAGES INCLUDE:

- Ideal for loading and unloading in confined spaces
- Reduced Maintenance™ features:
 - ✓ Fiberglass-reinforced Teflon® bearings at key pivot points, grease zerks, and closed-loop hydraulic system
- Cycle counter aids in forecasting maintenance checks
- Thermally protected super duty motor
- (2) 12-Volt Group 31 Batteries
- Powder coat finish on key liftgate components
- **INSTALLATION**
 - ✓ Universal side-mount kit (for steel or aluminum cross members) minimizes install time
 - ✓ Easy-Mount, bolt-on design for most dry-freight & refrigerated trailers
 - ✓ Compatible for both swing-type and roll-up doors
 - ✓ 100% Pre-Assembled & Tested before leaving the factory
 - ✓ Dual mud Flaps included to protect gate from road debris
- **SAFETY**
 - ✓ Meets or exceeds all TMC Electrical Wiring Recommended Practices
 - ✓ Roll-out Guard keeps your load on the platform
 - ✓ Hydraulic motor brake and cylinder lock ensures the platform stays in place
 - ✓ Locking chain secures the liftgate
 - ✓ Safety Reflectors (option to upgrade to flashing lights recommended)



The rear mounted GT and the side load GTSL help to maximize delivery efficiency with two liftgates.

SIDE LOADER GATE

Bed Ht: 48"-64 3/4"

Glide Trac GTSL overall width is 98"



Ideal for loading and unloading in confined spaces



Thermally protected power unit



Optional Cart Stop



Optional Side Access Ramp

SPECIFICATIONS:

Model	Capacity	Platform	Ramp
GTSL-33	3,300 lbs.	70" x 80"	12" Folding
GTSL-33	3,300 lbs.	80" x 80"	12" Folding
GTSL-44	4,400 lbs.	70" x 80"	12" Folding
GTSL-44	4,400 lbs.	80" x 80"	12" Folding

OPTIONAL EQUIPMENT:

- Platform Safety Lights
- Liftarm Safety Lights
- Hand-Held Remote allows driver to operate the liftgate from ground or bed level
- Side Ramps (30" x 16") with Auto-Latch
- Cart Stops (built into platform surface – will diminish usable load area)
- Dual Pump, Power Down Option for reliable performance in cold weather
- Trail Charger Kit provides a fully regulated 14-volt, 20-amp charge rate to remote liftgate batteries
- Galvanized Option
- Customized Options – contact factory

Waltco Lift Corp.
Corporate Office United States
285 Northeast Ave.
Tallmadge, OH 44278
P: 330.633.9191
F: 330.633.1418

Waltco Lift Corp.
United States
620 S Hambledon Ave.
City of Industry, CA 91744
P: 626.964.0990
F: 626.964.0149

Waltco Lift Inc.
Canada
265 Export Blvd.
Mississauga, ON L5S 1Y4
P: 888.343.4550

