

## Hiab XS 077 CLX Capacity 50,600 ft-lbs



Basic data

## Hiab XS 077 CLX Basic data

Technical data	B-1 CLX	B-2 CLX	B-3 CLX	E-3 CLX	E-4 CLX
Max. lifting capacity (ft-lbs)	51,370	49,200	47,750	46,310	44,140
Outreach - hydraulic extensions	18' 8"	24' 11"	31' 6"	31' 2"	38′ 1″
Outreach - manual extensions	30' 2"	37′ 1″	37′ 1″	37′ 9″	-
Outreach / Lifting capacity, standard (ft / lbs)	5′ 3″ / 9,260	5′ 3″ / 8,930	5′ 3″ / 8,710	6′ 11″ / 5,600	7′ 3″ / 5,200
	7'10" / 6,440	8′ 10″ / 5,560	9′ 10″ / 4,850	13′ 1″ / 3,530	13' 5" / 3,260
	12′ 6″ / 4,140	12' 6" / 3,920	12' 6" / 3,750	18′ 4″ / 2,430	18' 8" / 2,200
	17′ 9″ / 2,910	17′ 9″ / 2,690	17' 9" / 2,510	24' 7" / 1,720	24' 11" / 1,540
	-	23' 7" / 2,030	23′ 11″ / 1,810	30′ 10″ / 1,370	31' 2" / 1,190
	-	-	30' 2" / 1,410	-	38′ 1″ / 970
Slewing angle	406°	406°	406°	406°	406°
Height in folded position	75″	75″	75″	75″	75″
Width in folded position - 2300 base	83″	86″	88″	88″	92″
Installation space needed	27″	27″	29″	31″	28″
Weight - "standard" crane without stabilizers (lbs)	1,930	2,140	2,340	2,340	2,510
Weight - stabilizer equipment (lbs)	310 - 630	310 - 630	310 - 630	310 - 630	310 - 630

## Hiab XS 077 B-3 CLX





*Disclaimer.* Hiab cranes have been built to meet the highest standards of safety and service life and have been thoroughly tested. Strength calculations for this model have been carried out in accordance with EN13001 in fatigue class S2. Cargotec's certified Quality Assurance System complies with ISO 9001. Some of the items in our literature may be extra equipment. Certain applications may require an official permit. We reserve the right to change technical specifications without prior notice. Hiab cranes produced for EU-countries are CE-marked and comply with the European Standard EN 12999. *Cargotec* improves the efficiency of cargo flows by offering solutions for the loading and unloading of goods on land and at sea – wherever cargo is on the move. Cargotec's main daughter brands for cargo handling Hiab, Kalmar and MacGregor are global market leaders in their fields. www.cargotec.com

